

Micro-Nikkor 55mm f/3.5



Sales Points

- Perfect for normal shooting as well as close-ups.
- Focuses continuously from infinity to one half life-size; with the optional PK-13 Ring,* from one half to full life-size.
- Exceptional flatness of field for document and slide copying.
- Automatic diaphragm and full aperture metering.
- Two reproduction ratio scales engraved on the lens barrel for convenient reference.
- Minimum aperture of f/32 for additional depth of field.
- Deeply recessed front lens element eliminates the need for a separate lens hood.
- 52mm front thread accepts BR-2 Ring for reverse mounting on the camera.
- Weighs only 245 grams.

* PK-3 Extension Ring, with its pin-and-prong coupling mechanism, is still available for non-AI-type Nikon cameras. It offers the same amount of extension and automatic diaphragm operation as the PK-13.

Specifications

Focal length/maximum aperture:	55mm f/3.5
Mount:	Nikon bayonet type
Lens construction:	5 elements in 4 groups
Picture angle:	43°
Distance scale:	Graduated both in meters and feet from 0.241m, 9.5 in. to infinity (∞)
Aperture scale:	From f/3.5 to f/32; ADR scale also provided
Diaphragm:	Fully automatic
Reproduction ratios:	Scales provided on lens barrel; 1:10 to 1:2 for lens only; 1:2 to 1:1 for lens plus optional PK-3 or PK-13 Ring
Exposure measurement:	Via full-aperture method; meter-coupling ridge provided for AI cameras and meter-coupling shoe for non-AI cameras
Attachment size:	52mm (P = 0.75)
Dimensions:	66mm dia. x 64.5mm long
Length from lens mount:	53.5mm
Weight:	245g



Optional PK-13 Ring

